

IJSRNSC

Vol.8, Issue.2, April 2020 Research Paper

E-ISSN:2321-3256

Network Traffic Control Using AI

N. SelvaKumar^{1*}, M. Rohini², C. Narmada³, M. Yogeshprabhu⁴

^{1,2,3,4}Dept. of CSE, Coimbatore Institute of Engineering and echnology Tamil Nadu, India.

*Corresponding Author: selvaa618@gmail.com_Tel: +918870346752

Received: 1/Feb/2020, Accepted: 19/Mar/2020, Published: 30/Apr/2020

Abstract— The core of next generation 5G wireless network is heterogeneous network. The existing traditional 4G technology approaches are centrally managed and reactive conception-based network which needs additional hardware for every update and when there is a demand for the resources in the network. To reduce traffic in 4G network techniques like Port based, payload and feature based approach are used. They do not provide efficient resource management and it does not classify all type of network traffic effectively. 5G helps in giving solution to the problem of 4G network using prediction and traffic learning to increase performance and bandwidth. Heterogeneous network provides more desirable Quality of Service (QOS) and explores the resources of the network explicitly. The assortment of heterogeneous network brings difficulty in traffic control of the network. The problem in heterogeneous network is network traffic which cannot be controlled and managed due to different protocols and data transfer rate. The key problem of heterogeneous network is to achieve intelligent and efficient internet traffic control. The upcoming 5G heterogeneous network cannot be fulfilled until Artificial Intelligence is deployed in the network. This work aims to explore artificial intelligence inspired network traffic scheme for reducing traffic in a heterogeneous network. In this work the proposed system consists of clustering of traffic data set, statistical feature extraction of the network data, prediction of network traffic and classification of network traffic. The clustering of network data is implemented using Enhanced Density-based spatial clustering of applications with noise (DBSCAN) algorithm. The statistical feature of the network data is extracted and they are given as input into the Modified Backpropagation model for prediction and regression tree method is used for classification of network traffic. Finally caching and pushing of network is included to make use of the network resource effectively and also to provide finer Quality of Service (QOS) in a network.

Keywords— 5GNetwork; Artificial Intelligence; Machine Learning; Data Clustering; Statistical Feature; Traffic Prediction; Traffic classification.

I. INTRODUCTION

In recent years with the prosperous development of the Internet, networking has allured a lot of recognition in both industry and academia. The improvement of mobile communication has increased the data transfer rate significantly, for large amount of data with multimedia communication service. The mobile communication is now stepping into 5G. To satisfy the data traffic demand the network technology are moving towards heterogeneous network which provides ubiquitous internet access and enhanced public services [1].

The next generation network is service-driven where a single infrastructure should efficiently provide different service such as low latency communication, enhanced mobile broadband and immense machine type communication for heterogeneous network. The heterogeneous network different layers of cells like femto, macro, micro, pico, relays, diverse user devices and application.

The diversity of the heterogenous network results as a barrier for adopting numerous protocols and also it cannot manage the network resource effectively. The diversity of network leads to network traffic.





Artificial Intelligence plays a major role in overcoming the network traffic problem in heterogeneous network. In every possible field, machine learning has been used to leverage its astonishing power.

In variety of application such as speech recognition, bio informatics and computer vision, Machine Learning (ML) techniques have been used efficiently. Machine learning is mainly used for prediction and classification and also in

networking it is mainly used for performance prediction and intrusion detection. To make decision directly Machine learning constructs models that can learn themselves from data without being explicitly programmed or without following some set of rules.

Machine learning enables the model to get into selflearning mode without being explicitly programmed. The model can be trained by providing data sets to them, when exposed to new data, models are enabled to learn, predict and develop by themselves. Machine learning algorithm can be classified into three categories. They are supervised learning, unsupervised learning, reinforcement learning [3][5].

In Supervised learning the model is trained on a labeled data set which then learns on its own and when new testing data is given it compares with the training data set and predicts the output. Supervised learning is mainly used for regression and classification problems.

In unsupervised learning the training data set is unlabelled, and it finds pattern and relationship among data. It is mainly used in clustering and association problems. In reinforcement learning the model learns on its own without any training data.

This work mainly focuses on detection and classification of network traffic using machine learning techniques. The dataset is taken from network database. The data regarding the network flow are clustered depending on the flow of data and the number of clusters decided. The statistical features of the clustered data are extracted and given as input for classification model where the training and testing process is done and finally network traffic is predicted and classified.



Figure-2: Machine Learning Work Flow

The rest of the paper is organized as follows: In section 2 we discuss about the work that have been done related to classification and control of traffic. Section 3 and 4 we discuss about the proposed method that is used in this work. In section 5 we analyze experiment result. In section 6 we draw conclusion and discuss about future work.

II. RELATED WORK

The method of classifying traffic data set with relevant passive features that is observed in the traffic is called as phrase traffic classification. There are two type of classification goals. They are

• Fine grained

Coarse grained

In fine grained classification, exact classification of all network type application is done. The features of the application are selected exactly with relevant to the generated traffic. In coarse classification goals, only the transaction-oriented features are classified [13][14][15].

The traditional classification approaches for network classification using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) port number which has been used fifteen years ago cannot be used for accurate classification of traffic.

The traditional classification approach that has been used by researchers for network traffic classification are

- Port based IP traffic classification
- Payload based IP traffic classification

For exact classification of traffic new techniques have been used. They are

- Protocol Behavior or Heuristics Based Classification
- Classification based on flow statistics traffic properties [21]

A. Port based IP traffic classification

TCP and UDP give multiplexing of different streams between IP endpoints with the assistance of port numbers. Generally numerous applications use an 'outstanding' port to which different hosts may start correspondently. The application is deduced by looking into the TCP SYN parcel's objective port number in the Internet Assigned Numbers Authority (IANA's) rundown of enlisted ports. In any case, this methodology has constraints. Right off the bat, a few applications might not have their ports (for enrolled with IANA instance. distributed applications, for example, Napster and Kazaa). An application may utilize ports other than its outstanding ports to rescue from working framework get to control confinements. Additionally, at times server ports are powerfully assigned as required. Though port-based traffic grouping is the quickest and straightforward strategy, a few examinations have demonstrated that it performs ineffectively, e.g., under 70% precision in characterizing streams [11]12].

B. Payload based IP traffic classification

This methodology reviews the packet header to decide the applications. Packet payloads are analyzed a little bit at a time to find the bit streams that contain signature. In the event such piece of streams is discovered, at that point bundles can be precisely named. This methodology is regularly utilized for P2P traffic discovery and system interruption identification. Real impediments of this methodology are that the protection laws may not enable directors to assess the payload; it additionally forces huge multifaceted nature and preparing load on traffic ID

gadget; requires significant computationally power and capacity limit since it examines the full payload [2][17]

C. Protocol Behavior Based Classification

In this method the classification of networks is based on connection level patterns and network protocol behavior. This method is based on identifying and observing patterns of host behavior at the transport layer. The advantage of this classification is that packet pay load access is not needed [10][2].

D. Flow statistics Traffic Classification

The existing techniques are restricted by their dependence of packet content (payload and port numbers) on the inferred linguistics of the information gathered through deep review. Newer approaches depend on traffic's statistical characteristics to identify the applying [4][7][6][9] associate degree assumption underlying such ways in which is that traffic at the network layer has mathematical properties that are distinctive definitely classes of applications and modify different applications to be distinguished from each other. It uses network or transport layer that has applied mathematics properties like distribution of flow length, flow idle time, packet interarrival time, packet lengths etc. These are distinctive sure categories of applications and hence facilitate to differentiate different applications from one another.

This methodology is possible to see application sort however not usually the particular consumer type. as an example, it can't verify if flow belongs to Skype or Microsoft Network traveler voice traffic specifically [30][43]. The advantage of this approach is that there's no packet payload security is concerned.

E. Machine learning approach for traffic classification

Machine learning algorithms are effectively used for network traffic. It provides an alternative approach for payload and port-based approach. It is independent of packet length and features. Machine learning algorithm mainly involves testing and training process which gives more accurate result. Machine learning algorithms are classified as supervised, unsupervised, semi-supervised.

Supervised algorithms that are used for traffic classification are: Naïve Bayes, support vector machine, k- nearest neighbor. Unsupervised algorithm used for classification are K-Means and Density-based spatial clustering of applications with noise (DBSCAN).

Moore and Papagiannaki [32] observed no better than 70% byte accuracy for port-based classification using the official IANA list.

Madhukar and Williamson [33] showed that port-based analysis is unable to identify 30-70% of Internet traffic flows they investigated. Sen et al. [34] reported that the default port accounted for only 30% of the total traffic (in bytes) for the Kazaa P2P protocol.

Erman et al. in [31] in early 2007 proposed a semisupervised traffic classification approach which combines unsupervised and supervised methods. Motivations to the proposal are due to two main reasons: Firstly, labeled examples are scarce and difficult to obtain, while supervised learning methods do not generalize well when being trained with few examples in the dataset. Secondly, new applications may appear over time, and not all of them are known as a priori, traditional supervised methods map unseen flow instances into one of the known classes, without the ability to detect new types of flows [31].



Figure-3: Traffic Classification Approaches

The relationship between the class of traffic and its observed statistical properties has been noted in [36] (where the authors analyzed and constructed empirical models of connection characteristics - such as bytes, duration, arrival periodicity - for a number of specific TCP applications), and in [37] (where the authors analyzed Internet chat systems by focusing on the characteristics of the traffic in terms of flow duration, packet inter-arrival time and packet size and byte profile). Later work (for example [38] [39] and [40]) also observed distinctive traffic characteristics, such as the distributions of packet lengths and packet inter-arrival times, for a number of Internet applications. The results of these works have stimulated new classification techniques based on traffic flow statistical properties.

III. PROPOSED SYSTEM

In this paper an effective approach for network traffic detection and classification using machine learning approaches has been introduced. The proposed system includes methods such as data clustering, statistical feature extraction, detection and classification of network traffic. Caching and pushing of the traffic are implemented using collaborative filtering to make use of the resource



Figure-4: Flow Diagram of Proposed System

The network dataset is taken from the network database which does not contain any unwanted data. Initially network data is clustered using DBSCAN algorithm and then the statistical feature of the network data are extracted and unwanted flow of data is removed. The extracted features are given as input to the neural network classification model using testing and training process and finally, the network traffic is predicted, classified using regression tree and traffic control is made using the caching and pushing operations.

IV. METHODOLOGY

The proposed methodology for detection of network traffic using flow data packet is as follows:

- Step 1: Network data set acquisition.
- Step 2: Load data with flow construction
- Step3:Clustering of flow data packets using Enhanced DBSCAN clustering algorithm.
- Step 4: Statistical feature extraction of clustered data
- Step5:Prediction classification of feature extracted network data using modified neural network and regression tree.

A. Network Data set Acquisition

The dataset for network traffic classification is collected online from the network traffic website. The dataset consists of traffic flows which are randomly selected

© 2020, IJSRNSC All Rights Reserved

from the wide trace and carefully recognized by the manual inspection. It consists of 3416 instances with 7 classes such as (CHAT, FT, BROWSING, MAIL, STREAMING, VOIP, P2P) and it has 16 attributes.

Figure-5: Network Traffic Dataset

The 16 attributes in network traffic data are:

															lahiri Moorthi			
	Home	nset Page La	yart famili		exien Vien		il ne what you	went to do									A sha	
R	X Cat In Copy →	Calibri	• 11	• ĥ Ă	==	(), Wrap	led.	General		F. 🖗	9		Σka E Bit	oSam - AY	ρ			
Pale	🖋 Format Pa	ner B I	Ū · ⊡ ·	0 · A ·	5 5 5 <u>6</u>	E EMerge	& Center +	Q. % !	For	atting - Table -	s cel i Styles+	rseft Delete K	· Co	ar Hiter-	Find & Select •			
	Opbeard		fot			ignet		Nather	5	51/es		68		ERing				1
124			fe a															
1	A	В	С	D	E	F	G	н	1	J	К	L	М	N	0	р	Q	
1	Total_biat	min_fiat	min_biat	max_biat	mean_fiat	mean_biat	Flow_P/s	Flow_B/s	min_flow	max_flowi	mean_flow	std_flowia	min_active	mean_acti	min_idle	man_idle	Class	
2	2502257	2693576	3.91629	1411.64	4	3.5E+07	255901	1839548	1363299	5561680	3.5E+07	7589073	1079974	4426667	3.5E+07	7605741	CHAT	
3	2582052	2634447	3.82174	1731.1	4	3.5E+07	262235	1849452	1443143	4972742	3.5E+07	7131588	1065834	4185795	3.5E+07	7108954	CHAT	
4	3866535	4125707	1.91239	701.404	5	2.4E+07	525946	2842532	2757283	9991859	2.5E+07	8779228	1297996	9071855	2.4E+07	9259661	CHAT	
5	3213452	3322049	2.81599	1238.13	5	2.6E+07	357055	2313499	1566070	9245735	2.6E+07	9349672	1197148	8231822	2.6E+07	9321698	CHAT	
6	826.822	1154.76	0.075	6.08337	54824	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	826.822	3E+07	3E+07	3E+07	149.915	CHAT	
7	730.497	682.571	0.075	3.25002	57471	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	730.497	3E+07	3E+07	3E+07	200.043	CHAT	
8	994.136	1712.4	0.075	5.20836	57023	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	994.136	3E+07	3E+07	3E+07	495.613	CHAT	
9	6894311	6855915	0.3919	35.3902	79	2.4E+07	2608380	5402046	1212858	8380505	2.4E+07	7101680	1032008	8155093	2.4E+07	7116622	CHAT	
10	952.71	1043.78	0.0667	2.86804	57422	3E+07	1.7E+07	1.6E+07	3E+07	3E+07	3E+07	28602.4	3E+07	3E+07	3E+07	868.496	CHAT	
11	5425283	5458597	0.51399	53.1625	48	1.9E+07	1979695	4237096	1488138	8666237	2E+07	5322189	1316693	8323155	1.9E+07	5221816	CHAT	
12	1001.49	967.98	0.075	5.46672	54803	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	27794.2	3E+07	3E+07	3E+07	1006	CHAT	
13	1139.65	100341	0.075	5.20845	57271	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	29949.1	3E+07	3E+07	3E+07	60771.6	CHAT	
14	0	0	11.1993	481.569	178583	178583	178583	0	-1	0	-1	0	-1	0	-1	0	CHAT	
15	4466429	4422333	0.63162	56.8899	70	2.1E+07	1605858	3456926	1423241	6225957	2.1E+07	4760101	1252013	5859592	2.1E+07	4758397	CHAT	
16	55.7659	8083.02	0.075	3.2	57418	3E+07	1.5E+07	1.6E+07	3E+07	3E+07	3E+07	28911.4	3E+07	3E+07	3E+07	4895.22	CHAT	
17	93.626	11991.5	0.08883	6.84027	54473	3E+07	1.3E+07	1.6E+07	3E+07	3E+07	3E+07	93.626	3E+07	3E+07	3E+07	7051.8	CHAT	
18	0	0	57142.9	2285714	35	35	35	0	-1	0	-1	0	-1	0	-1	0	FT	
19	159.84	234.294	22079	2.6E+07	1	1092	45.4871	115.462	-1	0	-1	0	-1	0	-1	0	FT	
20	191.292	0	7374.86	294995	22	706	138.543	191.292	-1	0	-1	0	-1	0	-1	0	FT	
21	754.351	873.956	3508.77	391707	28	1758	313.5	517.759	-1	0	-1	0	-1	0	-1	0	FT	

min_active	Minimum time a flow was active before becoming idle				
mean_active	Mean time a flow was active before becoming idle				
max_active	Maximum time a flow was active before becoming idle				
std_active	Standard deviation time a flow was active before				
	becoming idle				
min_idle	Minimum time a flow was idle before becoming active				
mean_idle	Mean time a flow was idle before becoming				
	active				
max_idle	Maximum time a flow was idle before becoming active				
min_biat	Minimum time between two packets sent in the				
	backward direction				
max_fiat	Maximum time between two packets sent in the				
	forward direction				
max_biat	Maximum time between two packets sent in the				
	backward direction				
mean_fiat	Mean time between two packets sent in the forward				
	direction				
mean_biat	Mean time between two packets sent in the backward				
	direction				
flowPktsPerSeco	Number of flow packets per second				
nd					
flowBytesPerSec	Number of flow bytes per second				
ond					
min_flowiat	Minimum inter-arrival time of packet				
max_flowiat	Maximum inter-arrival time of packet				
mean flowiat	Mean inter-arrival time of packet				

B. Clustering of Network Dataset Using Modified DBSCAN

Density Based Spatial Clustering of Application of Noise is a density- based clustering algorithm which uses dense area of objects. The parameters that are used in DBSCAN algorithm are eps, min points. The clusters in DBSCAN are formed from the core point which are directly-density reachable and density reachable [18].

The parameters that are used for accurate classification are Threshold parameter, Minimum points, Distance measure function

The data are collected from online tools and features are selected based on the packets and then they are fit into the model for testing and training. Finally, they are predicted and classified.

Let $Y = \{Y1, Y2, Y3...\}$ be the set of data points

- Initially the process has to be started with an arbitrary starting point which is not visited already.
- Extract the neighbour of arbitrary point using ε.
- Then clustering process starts if there are sufficient neighbourhood and point is marked as visited or it is noted as noise data.
- If a point is found to be a part of the cluster then its ε neighbour is also the part of the cluster and the above procedure from step 2 is repeated for all ε neighbour points. Until all the cluster point is determined this process is repeated.
- The unvisited new point is retrieved.
- This process stops when all points are marked as visited. The proposed method also includes Fixed Radius

Nearest Neighbour Calculation of the clustering the network data which increases the accuracy of the clustering process. Here the frNN is calculated from the output that is obtained from res<- dbscan.

res <- dbscan(data, eps=0.5, MinPts = 7) res #pairs(data, col = res\$cluster + 1L) fr <-

frNN(data, eps = .5) dbscan(fr,

minPts = 7)



Figure-6: Data clustered using Enhanced DBSCAN

© 2020, IJSRNSC All Rights Reserved

C. Statistical Feature Extraction of the Network Data

After clustering of network data, the statistical features of the network data are extracted which is then move forward to classification process. The statistical features help in classifying and predicting the network data in more accurate manner. There are many types of statistical features some of them have been extracted in this method [23][28].

The statistical feature contains

- Packets
- Bytes
- Packet size
- Inter packet time

Types Of	Feature Description	Numbe
Features		r
Packets	Number of packets	2
	transferred	
Bytes	Volume of bytes	2
	transferred	
Packet Size	Min, Max, Median and	8
	Standard.	
	Deviation of packet size	
Inter Packet	Min, Max, Median and	8
Time	Standard. Deviation of	
	inter packet time	
	Total	20

D. Network Traffic Classification Using modified Backpropagation and Regression Tree

Artificial neural network is one of the learning algorithms

$$\Delta_{W_{ij_x}} = -\varepsilon \frac{\delta E}{\delta_{W_{ii}}} = \varepsilon \delta_{a_{i_x}}$$

where which is used within machine learning techniques. It consists of many layers for learning and analysing data [43][42]. It learns like human brain and it is mainly used for pattern recognition and data classification. Neural networks are trained using examples. They can be programmed explicitly. It contains three layers

- Input layer
- Hidden layer
- Output layer

It may also contain multiple hidden layer. Hidden layer is mainly used for feature extraction and calculation. Feed forward and feedback are two topologies in neural network [22].

It is the most important algorithm for training a neural network. It is mainly used to network traffic effectively in heterogenous network. For training the weights in multi layer feed forward network, backpropagation algorithm is used [27].

The neuron has weights that has to be maintained. Then the forward propagation is classified as neuron activation, neuron transfer, forward propagation [26][29].

Next is backpropagate error where the error is calculated and error is then back propagated through the hidden layer. It involves transfer derivate and error propagation. Then the network has to be trained by propagating the error and forwarding inputs [16].

The proposed backpropagation algorithm includes In the context of learning, backpropagation is commonly used by the gradient decent optimization algorithm to adjust the weight of neurons by calculating the gradient of the loss function.

Gradient Descent learning requires that any change in a particular weight be proportional to the negative of the derivative of the error, the change in a given weight must be proportional to the negative of our prior equation. Replacing the difference between the target and actual activation of the relevant output node by d, and introducing a learning rate epsilon, that equation can be re-written in the final form of the Delta Rule [19][20][12]:

The proposed algorithm for prediction of network traffic using neural network

radientDesc <function(x, y, learn_rate, conv_threshold, n, max_iter) { while(converged == F) {

Implement the gradient descent algorithm

```
m_new <- m - learn_rate * ((1 / n) * (sum((yhat - y) *
x))) c_new <- c - learn_rate * ((1 / n) * (sum(yhat -
y)))</pre>
```

m <-

m_new

c <-

c_new

yhat <- m * x + c

 $MSE_new <- sum((y - yhat) ^ 2) /$

```
n if(MSE - MSE_new <=
```

```
conv_threshold) { abline(c, m)
```

converged = T

m))

```
return(paste("Optimal intercept:", c, "Optimal slope:",
```

}

iterations = iterations

+ 1 if(iterations >

max_iter) { abline(c, m)

```
converged = T
```

return(paste("Optimal intercept:", c, "Optimal slope:", m))



Figure-7: Neural Network Learning Process using modified Backpropagation algorithm- Gradient Decent

The class which are predicted in proposed system are

- CHAT
- FT
- BROWSING,
- MAIL
- STREAMING
- VOIP
- P2P



v) STREAMING vi) BROWSING

Figure-8:Prediction of different class in network traffic-i) Class VOIP ii) CHAT iii)MAIL iv) P2P v) STREAMING vi) BROWSING



Figure-9: Classification of network traffic

The predicted classes are then classified using regression tree algorithm with different traffic parameters.

E. Caching and Pushing using Collaborative filtering.

The main aim of caching and pushing is to use the resource effectively and also to improve the Quality of Service in the network.

By analysing users' information, habits, and historical data, recommendation algorithms can implement caching and pushing efficiently in the network which increases the accuracy of the system.

There are two types of collaborative filtering algorithm. They are:

- User based
- Item based

The user-based collaborative filtering algorithm will cache and push information based on the similarity between users; for example, caching video play to a user who has high similarity with the target user.

The item-based collaborative filtering algorithm will push and cache data based on the historical data of the base station; for example, caching the next episode of a TV series automatically.

V. EXPERIMENTAL RESULT

The proposed system classifies 3416 instances with seven classes and controls network traffic using Backpropagation classifier. The network traffic dataset is tested and classified. The classification performance is measured by sensitivity, specificity, accuracy, error rate F- measure, Precision and Recall.

Sensitivity =
$$\frac{TP}{TP + FN}$$

Specificity = $\frac{TN}{TN + FP}$
Accuracy = $\frac{TP + TN}{TP + FN + TN + FP}$
F - Measure = $\frac{2TP}{2TP + FP + FN}$

Here Sensitivity denotes true positive rate and specificity explores true negative rate. Accuracy represents proportion of true positive and negative rate. Precision represents the ration of True positives over the sum of True Positives and False Positives. Recall indicates the ratio of True Positives over the sum of True Positives and False Negatives.

The sensitivity of the proposed system improved 92% to 97% which is positive proportion of the system.

The specificity of the work reduced from 70% to 65%. Specificity indicates the negative rate of the prediction system.

The error rate of the proposed system gradually decreased from 0.45 % to 0.32%.

The F-measure of the system improved from 0.96 to 0.90%.

Vol.8, Issue.2, Apr 2020

By applying weight optimization in neural network using soft computing technique gradient decent algorithm, the overall performance of the proposed system improved to 97.6 from 96.2%. The Performance of the proposed and existing system is represented in bar chart.



a) Accuracy comparison

b) Sensitivity Comparison





e) F-measure comparison

Figure-10: Bar Chart Comparison of Existing and proposed Method- a) Accuracy comparison b) Sensitivity Comparisonc) Specificity Comparison d) Error Rate e) F-measure comparison.

VI. CONLCUSION

AI is used as a tool to improve 5G technologies in recent technologies. The core of next generation 5G wireless

network is heterogeneous network. Network traffic is the biggest problem of heterogeneous network which reduces QOS of network. To provide better service and also to use resource effectively traffic has to be monitored and controlled. The problem of 5G network can be solved using Machine Learning techniques. In this work AI inspired traffic control scheme is introduced. The clustering of network data is implemented using Enhanced Density-based spatial clustering of applications with noise (DBSCAN) algorithm. The statistical feature of the network data is extracted and they are given as input into the Modified Backpropagation model for prediction and regression tree method is used for classification of network traffic. Finally caching and pushing of network is included to make use of the network resource effectively and also to provide finer Quality of Service (QOS) in a network. The performance of the Proposed system achieved is about 97.6 and it is calculated using the parameters accuracy, sensitivity, specificity, error rate and F-Measure.

REFERENCES

- L. C. I, S. Han, Z. Xu, et al, New paradigm of 5G wireless internet [J], IEEE Journal on Selected Areas in Communications, Vol.34, No.3,474-482,2016.
- [2] R. Li, Z. Zhao, X. Zhou, et al, Intelligent 5G: when cellular networks meet artificial intelligence[J], IEEE Wireless Communications, PP(99) ,2-10,2017
- [3] S. Dzulkifly, L. Giupponi, F. Sai, et al, Decentralized Q learning for uplink power control[C], IEEE, International Workshop on Computer Aided Modelling and Design of Communication Links and Networks, IEEE, 54-58, 2015.
- [4] M. Shafi et al.,"5G: A Tutorial Overview of Standards, Trials, Challenges, Deployment, and Practice," IEEE JSAC, vol. 35,no. 6, pp. 1201–21. June 2017
- [5] D. Soldani, A. Manzalini, Horizon 2020 and beyond: on the5G operating system for a true digital society [J], IEEE Vehicular Technology Magazine, Vol.10, No.1, 32-42,2015.
- [6] Y. Zhang et al., "Home M2M Networks: Architectures, Standards, and QoS Improvement," IEEE Commun. Mag.,vol. 49, no. 4, Apr. 2011, pp. 44–52.
- [7] Chen Z, Wen J, Geng Y. Predicting future traffic using hidden markov models. In: Proceedings of 24th IEEE International Conference on
 - Network Protocols (ICNP). IEEE; 2016. p. 1-6.
- [8] I. Portugal, P. Alencar, and D. Cowan, "The Use of MachineLearning Algorithms in Recommender Systems: A Systematic Review," Expert Systems with Applications, vol. 97, May 2018, pp. 205–27.
- [9] S. Maharjan et al., "Dependable Demand Response Management in the Smart Grid: A Stackelberg Game Approach," IEEE Trans. Smart Grid, vol. 4, no. 1, 2013, pp. 120–32.
- [10] G. Alnwaimi, S. Vahid, and K. Moessner, "Dynamic heterogeneous learning games for opportunistic access in LTE-based macro/femtocell deployments," IEEE Transactions on Wireless Communications, vol. 14, no. 4, pp. 2294–2308, 2015.
- [11] D. D. Nguyen, H. X. Nguyen, and L. B. White, "Reinforcement Learning with Network-Assisted Feedback for Heterogeneous RAT Selection," IEEE Transactions on Wireless Communications, vol. 16, no. 9, pp. 6062–6076, 2017.

- [12] Rathidevi M and Dr. S.V. Sudha, "Implementing Artificial Neural Network in Enhanced Micro Blog for Social Network, E Commerce and News Channels," on International Research Journal in Advanced Engineering and Technology, Vol 3 Issue 3, ISSN: 2454-4744, E- ISSN: 2454-4752, pp. 2527-2533, 2017.
- [13] U. Challita, L. Dong, and W. Saad, "Deep learning for proactive resource allocation in LTE-U networks," in European Wireless 2017- 23rd European Wireless Conference, 2017.
- [14] R. Pascanu, T. Mikolov, and Y. Bengio, "On the difficulty of training recurrent neural networks," Tech. Rep., 2013.
- [15] C. Jiang, H. Zhang, Y. Ren, Z. Han, K. C. Chen, and L. Hanzo, "Machine Learning Paradigms for Next-Generation Wireless Networks," *IEEE Wireless Communications*, 2017.
- [16] T. E. Bogale, X. Wang, and L. B. Le, "Machine Intelligence Techniques for Next-Generation Context-Aware Wireless Networks," *ITU Special Issue: The impact of Artificial Intelligence (AI) on communication networks and services.*, vol. 1, 2018
- [17] G. Villarrubia, J. F. De Paz, P. Chamoso, and F. D. la Prieta, "Artificial neural networks used in optimization problems," *Neurocomputing*, vol. 272, pp. 10–16, 2018.
- [18] B. Bojovic', E. Meshkova, N. Baldo, J. Riihijärvi, and M. Petrova, "Machine learning-based dynamic frequency and bandwidth allocation in self-organized LTE dense small cell deployments," *Eurasip Journal on Wireless Communications* and Networking, vol. 2016, no. 1, 2016.
- [19] E. Balevi and R. D. Gitlin, "Unsupervised machine learning in 5G networks for low latency communications," 2017 IEEE 36th International Performance Computing and Communications Conference, IPCCC 2017, vol. 2018-Janua, pp. 1–2, 2018.
- [20] Sadasivam Vijayakumar Sudha and Keppanagowder Thanushkodi, "A Genetic Based Neuro Fuzzy Technique for Process Grain Sized Scheduling of Parallel Jobs," Journal of Computer Science, pp. 48-54, ISSN 1549-3636, Science Publication 2012.
- [21] U. Challita, L. Dong, and W. Saad, "Deep learning for proactive resource allocation in LTE-U networks," in European Wireless 2017- 23rd European Wireless Conference, 2017
- [22] R. Pascanu, T. Mikolov, and Y. Bengio, "On the difficulty of training recurrent neural networks," Tech. Rep., 2013
- [23] Q. V. Le, N. Jaitly, and G. E. Hinton Google, "A Simple Way to Initialize Recurrent Networks of Rectified Linear Units," Tech. Rep., 2015.
- [24] G. Alnwaimi, S. Vahid, and K. Moessner, "Dynamic heterogeneous learning games for opportunistic access in LTE-based macro/femtocell deployments," IEEE Transactions on Wireless Communications, vol. 14, no. 4, pp. 2294–2308, 2015.
- [25] D. D. Nguyen, H. X. Nguyen, and L. B. White, "Reinforcement Learning with Network-Assisted Feedback for Heterogeneous RAT Selection," IEEE Transactions on Wireless Communications, vol. 16, no. 9, pp. 6062–6076, 2017.
- [26] M. S. Parwez, D. B. Rawat, and M. Garuba, "Big data analytics for user-activity analysis and user-anomaly detection in mobile wireless network," IEEE Transactions on Industrial Informatics, vol. 13, no. 4, pp. 2058–2065, 2017.
- [27] S.V. Sudha, K. Thanushkodi, "Use of Neural Network with Hybrid Intelligent Optimization Techniques for Weight Determination in Parallel Job Scheduling," Scientific Research and Essays, Vol.7(26), pp.2310-2333, 12 July 2012.

- [28] U. Challita, L. Dong, and W. Saad, "Deep learning for proactive resource allocation in LTE-U networks," in European Wireless 2017- 23rd European Wireless Conference, 2017.
- [29] L.-C. Wang and S. H. Cheng, "Data-Driven Resource Management for Ultra-Dense Small Cells: An Affinity Propagation Clustering Approach," IEEE Transactions on Network Science and Engineering, vol. 4697, no. c, pp. 1–1, 2018.
- [30] S. P. Sotiroudis, K. Siakavara, and J. N. Sahalos, "A Neural Network Approach to the Prediction of the Propagation Pathloss for Mobile Communications Systems in Urban Environments," *PIERS Online*, vol. 3, no. 8, pp. 1175–1179, 2007.
- [31] T. M. Mitchell, *Machine Learning*, 1st ed. McGraw-Hill Science/Engineering/Math, 1997.
- [32] T. Zhou, L. Chen, and J. Shen, "Movie Recommendation System Employing the User-Based CF in Cloud Computing," Proc. 2017 IEEE Int'l. Conf. Computational Science and Engineeringand Embedded and Ubiquitous Computing, vol. 2. 2017, pp. 46–50.
- [33] P. U. Stanford Vision Lab, Stanford University, "ImageNet." [Online]. Available: <u>http://image-net.org/about-overview</u>
- [34] J. Erman, A. Mahanti, M. Arlitt, I. Cohen, and C. Williamson, "Semisupervised network traffic classification," ACM International Conference on Measurement and Modeling of Computer Systems (SIGMETRICS) Performance Evaluation Review, vol. 35, no. 1, pp. 369–370, 2007
- [35] A. Moore and K. Papagiannaki, "Toward the accurate identification of network applications," in Proc. Passive and Active Measurement Workshop (PAM2005), Boston, MA, USA, March/April 2005.
- [36] A. Madhukar and C. Williamson, "A longitudinal study of P2P traffic classification," in 14th IEEE International Symposium on Modeling, Analysis, and Simulation of Computer and Telecommunication Systems, September 2006.
- [37] S. Sen, O. Spatscheck, and D. Wang, "Accurate, scalable in network identification of P2P traffic using application signatures," in WWW2004, New York, NY, USA, May 2004.
- [38] J. Erman, A. Mahanti, and M. Arlitt. Byte Me: A Case for Byte Accuracy in Traffic Classification. In ACM SIGMETRICS MineNet Workshop, June 2007
- [39] V. Paxson, "Empirically derived analytic models of wide-area TCP connections," IEEE/ACM Transactions on Networking, vol. 2, no. 4, pp. 316–336, 1994.
- [40] C. Dewes, A. Wichmann, and A. Feldmann, "An analysis of Internet chat systems," in ACM/SIGCOMM Internet Measurement Conference 2003, Miami, Florida, USA, October 2003.
- [41] K. Claffy, "Internet traffic characterisation," PhD Thesis, University of California, San Diego, 1994.
- [42] T. Lang, G. Armitage, P. Branch, and H.-Y. Choo, "A synthetic traffic model for Half-life," in Proceedings of Australian